

FANUC M-430iA/2FH



The FANUC M-430iA/2FH is ideal for packaging, assembly, and part transfer applications. With a slim design, this FANUC M430iA/2FH can work in tight spaces. The M 430iA/2FH has 5 axes, a 2 kg payload, and is certified to work with food handling. Advance your production today with a FANUC M-430iA/2FH robot!

For more information about the FANUC M-430iA/2FH, contact a Robotworx representative today at 740-251-4312.

Robot Information

Robot Specifications

Axes:..... **5**
 Payload:..... **2 kg**
 H-Reach:..... **900 mm**
 Repeatability: **±0.5 mm**
 Robot Mass: **55 kg**
 Structure: **Articulated**
 Mounting: **Floor, Inverted, Angle**

Robot Motion Speed

J1..... **300°/s (5.24 rad/s)**
 J2..... **320°/s (5.59 rad/s)**
 J3..... **320°/s (5.59 rad/s)**
 J4..... **360°/s (6.28 rad/s)**
 J5..... **2000°/s (34.91 rad/s)**

Robot Motion Range

J1..... **±360°**
 J2..... **±230°**
 J3..... **±383°**
 J4..... **±300°**
 J5..... **±540°**

Robot Controllers

R-30iB >

Robot Applications

Assembly > Packaging >
 Meat Processing Automation > Part Transfer >
 Order Picking >