

KUKA KR 60 HA



This high accuracy Kuka KR 60 HA model is ideal for intricate applications such as laser beam welding, MIG/MAG welding, and machining.

Apart from precision, the Kuka KR 60 HA KR C2 offers other advantages. Reliability and versatility are chief among these. Install this 6-axis robot from the floor or ceiling. The Kuka KR 60 HA KR C2 comes in three different versions, each with a different payload and reach limit.

Save money and space when you buy the Kuka High Accuracy KR 60 HA. A small footprint and streamlined look benefit any manufacturing floor.

For more information about the KUKA KR 60 HA, contact a Robotworx representative today at 740-251-4312.

Robot Information

Robot Specifications

Axes:..... 6
 Payload:..... 60 kg
 H-Reach:..... 2033 mm
 Repeatability: ± 0.05 mm
 Robot Mass: 665 kg
 Structure: Articulated
 Mounting: Floor, Inverted

Robot Motion Speed

J1.....140 °/s (2.44 rad/s)
 J2.....120 °/s (2.09 rad/s)
 J3.....140 °/s (2.44 rad/s)
 J4.....260 °/s (4.54 rad/s)
 J5.....245 °/s (4.28 rad/s)
 J6.....322 °/s (5.62 rad/s)

Robot Motion Range

J1.....±185°
 J2.....+35° - 135°
 J3.....+158° - 120°
 J4.....±350°
 J5.....±119°
 J6.....±350°

Robot Controllers

KUKA KR C2 >

Robot Applications

3D Laser Vision Robots >
 Assembly Robots >
 Coating Robots >
 Cutting Robots >

Deburring Robots >
 Machine Loading Robots >
 Material Removal Robots >
 Meat Processing Automation >